

EF 613 - OIL / FUEL DELIVERY HOSE W.P. 10 BAR

Construction**Core** Black colour, Synthetic rubber resistant to oil**Reinforcement** Plies of synthetic textile cords with two cross anti static copper wires**Cover** Black colour, Synthetic rubber resistant to oil, ozone and abrasion**Application** Mandrel built heavy duty oil suction and discharge hose for handling grades of gasoline or petroleum oils of aromatic content upto 50% from tank truck, in dispensing station etc, during winter/summer seasons and withstands full vacuum

Item Code	Dash Size	ID		OD		WP		BP		W
		inch	mm	inch	mm	psi	bar	psi	bar	
EF613-12	-12	3/4	19.0	1.06	27.0	150	10	435	30	0.52
EF613-16	-16	1	25.0	1.38	35.0	150	10	435	30	0.65
EF613-20	-20	1.1/4	32.0	1.65	42.0	150	10	435	30	0.80
EF613-24	-24	1.1/2	38.0	1.89	48.0	150	10	435	30	0.94
EF613-32	-32	2	51.0	2.44	62.0	150	10	435	30	1.26
EF613-40	-40	2.1/2	63.0	2.95	75.0	150	10	435	30	1.90
EF613-48	-48	3	76.0	3.46	88.0	150	10	435	30	2.20
EF613-56	-56	3.1/2	89.0	4.09	104.0	150	10	435	30	2.60
EF613-64	-64	4	102.0	4.57	116.0	150	10	435	30	2.85
EF613-80	-80	5	127.0	5.59	142.0	150	10	435	30	4.20
EF613-96	-96	6	152.0	6.54	166.0	150	10	435	30	5.30

**Temperature Range:** Continuous: -20°C to +80°CEF 614 - OIL **SUCTION** & DISCHARGE HOSE **W.P. 20 BAR****Construction****Core** Black colour, Synthetic rubber resistant to oil**Reinforcement** Plies of synthetic textile cords with steel helix and two cross anti static copper wire**Cover** Black colour, Synthetic rubber resistant to oil, ozone and abrasion**Application** Mandrel built heavy duty oil suction and discharge hose for handling grades of gasoline or petroleum oils of aromatic content upto 50% from tank truck, in dispensing station etc, during winter/summer seasons and withstands full vacuum

Item Code	Dash Size	ID		OD		WP		BP		V	W
		inch	mm	inch	mm	psi	bar	psi	bar	bar	kg/m
EF614-12	-12	3/4	19.0	1.14	29.0	300	20	870	60	0.90	0.60
EF614-16	-16	1	25.0	1.38	35.0	300	20	870	60	0.90	0.86
EF614-20	-20	1.1/4	32.0	1.65	42.0	300	20	870	60	0.90	1.03
EF614-24	-24	1.1/2	38.0	1.93	49.0	300	20	870	60	0.90	1.20
EF614-32	-32	2	51.0	2.48	63.0	300	20	870	60	0.90	1.80
EF614-40	-40	2.1/2	63.0	3.03	77.0	300	20	870	60	0.90	2.40
EF614-48	-48	3	76.0	3.54	90.0	300	20	870	60	0.90	2.90
EF614-56	-56	3.1/2	89.0	4.09	104.0	300	20	870	60	0.90	3.60
EF614-64	-64	4	102.0	4.65	118.0	300	20	870	60	0.90	4.10
EF614-80	-80	5	127.0	5.63	143.0	300	20	870	60	0.90	6.80
EF614-96	-96	6	152.0	6.77	172.0	300	20	870	60	0.90	9.00
EF614-128	-128	8	203.0	8.94	227.0	300	20	870	60	0.90	14.00

**Temperature Range:** Continuous: -20°C to +80°C