



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1275160	13	1/2	22	0,87	10	150	30	450	0,31	0,21	60	200
1270923	25	1	38	1,50	10	150	30	450	0,81	0,54	60	200
1317164	32	1-1/4	48	1,89	10	150	30	450	1,26	0,84	60	200
1271172	38	1-1/2	56	2,21	10	150	30	450	1,65	1,11	60	200
1286706	40	1-3/4	60	2,36	10	150	30	450	1,93	1,30	60	200
1355716	51	2	71	2,80	10	150	30	450	2,39	1,61	60	200
1385259	63,5	2-1/2	84,5	3,33	10	150	30	450	3,07	2,06	60	200
1279564	76	3	101	3,98	10	150	30	450	4,24	2,85	60	200



EN

Premium delivery hose for non fatty foods

Standards: Reg. EC 1935/04 and EC 2023/06. Phthalates free. PAHs free (acc. to ZEK 01.4-08 Cat. 1). Bisphenol A free. Heavy metal tested. FDA tit.21 art.177.2600 aqueous foods. BfR XXI Cat.2 foods. D.M. 21/03/73 aqueous and alcohol up to 96°.

Application: softwall hose for delivery of vintage wines and alcohols at 96°. Designed for use in breweries and distilleries, completely odourless and taste-free.

Temperature: from -40°C (-40°F) to +120°C (+248°F).

Construction

Tube: white, smooth, food quality, taste free and odourless IIR rubber.

Reinforcement: high strength synthetic cord, separated by a layer of rubber.

Cover: red, smooth (wrapped finish), food quality IIR rubber, weathering resistant.

Branding: continuous red/white stripe "IVG Food...".

Also available upon request: 1. Different diameters 2. Hose cover in different colours 3. Different working pressures.

CN

高级食品输送管

质量标准: FDA tit.21 item 177.2600 液态食物. BfR XXI Cat.2 食品类 D.M. 21/03/73 液态食物和96° 酒精. PHTHALATES free. CE 1935/04, CE 2023/06

应用范围: 软壁胶管, 用于传输葡萄酒, 及高达96° 酒精含量的食品. 设计用于酿酒业, 蒸馏业, 无异味. 不含塑化剂

温度范围: -40° C (-40° F) 到 +120° C (+248° F)

软管结构

内层: 白色, 光滑, 食品级的IIR橡胶, 无异味

加强层: 橡胶层分隔的高强度合成线绳

外层: 红色, 光滑, 食品级IIR橡胶, 耐侵蚀

商标: 连续红/白色条形标记 "IVG Food ..."

可选择项: 1. 不同口径 2. 各种外层颜色 3. 各种工作压力