



尚府貿易股份有限公司

<https://www.sunflexhose.com.tw>

FUEL & OIL HOSE(SAE J30 R6)

For use on fuel and oil transport lines attached to gas and construction equipment

Structure

- Tube : High-quality nitrile synthetic rubber (High oil resistance)
- Reinforcement : Spiral synthetic yarn
- Cover : Abrasion, oil, weather & ozone resistant synthetic rubber (NBR/SBR)

Specification

- Temperature : -40°F ~ 210°F (-40°C ~ 100°C)
- Color : Black



※ Branding

HS EXwill

FUEL & OIL HOSE = SAE J30 R6 = ***MM(****) I.D MAX. W.P 20BAR

Part No.											
	I,D		O,D		Max. W,P		Min. B,P		Bend Radius		Approx. Weight
	inch	mm	inch	mm	bar	psi	bar	psi	kg/m	lb/ft	m
FOH1B											
FOH1B-048	3/16	4.8	0.47	12.0	20	300	60	900	0.12	0.08	100
FOH1B-064	1/4	6.4	0.52	13.3	20	300	60	900	0.14	0.09	100
FOH1B-079	5/16	7.9	0.59	15.0	20	300	60	900	0.17	0.11	100
FOH1B-095	3/8	9.5	0.65	16.5	20	300	60	900	0.19	0.13	100
FOH1B-127	1/2	12.7	0.79	20.0	20	300	60	900	0.25	0.17	100
FOH1B-159	5/8	15.9	0.94	24.0	20	300	60	900	0.35	0.24	50
FOH1B-191	3/4	19.1	1.14	29.0	20	300	60	900	0.51	0.34	50
FOH1B-254	1	25.4	1.54	39.0	20	300	60	900	0.94	0.63	50